

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)



The
Patent
Office

PCT/GB 99/0936

INVESTOR IN PEOPLE

09/806962

REC'D 26 JUL 1999	
WIPO	PCT

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Signed


Andrew Gersey

Dated

5 July 1999

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)



06 OCT 98 E395032-1 003008
F01/7700 0.00 - 9821658.3

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form))

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

05 OCT 1998

1. Your reference

ACR/SH-57525

2. Patent application number

(The Patent Office will fill in this part)

9821658.3

3. Full name, address and postcode of the or of each applicant (underline all surnames)

John Francis DUFORT
91 Egloshayle Road
Wadebridge
Cornwall
PL27 6AF

Patents ADP number (*if you know it*)

If the applicant is a corporate body, give the country/state of its incorporation

7525892001

4. Title of the invention

PLASTICS ARTICLE AND METHOD OF MANUFACTURE

5. Name of your agent (*if you have one*)

LLOYD WISE, TREGEAR & CO

"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)

COMMONWEALTH HOUSE
1-19 NEW OXFORD STREET
LONDON WC1A 1LW

Patents ADP number (*if you know it*)

AL002

117001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number
(*if you know it*)

Date of filing
(*day / month / year*)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(*day / month / year*)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer "Yes" if:

NO

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body:
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description 9

Claim(s)

Abstract

Drawing(s) 1 *21 3*

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(*please specify*)

11.

I/We request the grant of a patent on the basis of this application

Signature *Howe*

Date 5 October 1998

12. Name and daytime telephone number of person to contact in the United Kingdom

STEVEN HOWE
0171 571 6200

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered "Yes" Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

PLASTICS ARTICLE AND METHOD OF MANUFACTURE

In the late nineteenth and early twentieth centuries, lithophanes were formed from porcelain. These objects were pieces of porcelain which were formed with sections of various thickness corresponding to the light and dark parts of an image, with the darker sections formed as thicker portions of the porcelain and lighter sections formed as thinner sections of the porcelain. The porcelain was fired at a very high temperature, resulting in the porcelain becoming translucent. By shining light through the porcelain from behind, as a result of the different thicknesses of the porcelain and therefore the different transmissivity of light through the porcelain, the image is seen, with the different intensities of light passing through the porcelain corresponding to the different areas of light and shade of the original image.

In the early part of the twentieth century, lithophanes were formed by engraving a mould from wax with the relief of the mould corresponding to the areas of different brightness of the desired image, and these were used to mould ceramic to form the lithophane. Such lithophanes were used as window hangings, fire screens, teapot warmers and lamps.

From around the 1930's, there was no longer any interest in lithophanes, and they are rarely seen today.

The present invention relates to a plastics article having different thicknesses corresponding to the different intensities of an image, and to a method of forming such a plastics article, the resulting article having a similar appearance to a porcelain lithophane.

According to a first aspect of the present invention, a method of forming a plastics article comprises the steps of:

- 5 determining the relative intensity at different points of an image;
- machining a mould to give a relief corresponding to the relative intensity of the points of the original image; and,
- 10 moulding the plastics article from a translucent material in the mould to form a plastics article having different thicknesses corresponding to the different intensities of the original image.

- 15 It has been found that an article giving a similar visual appearance to a lithophane formed from porcelain can be formed from a plastics material. Such an article is advantageous over a porcelain lithophane in that it is significantly cheaper and easier
- 20 to manufacture, does not require firing at a high temperature and is less susceptible to damage. Further, by selection of a suitable plastics material, it is possible to see the image when the article is back lit by
- 25 source. By moulding the article, for example by injection moulding techniques, mass reproduction is possible.

- 30 It is preferred that the determination of the relative intensity of the different points of the image is achieved by scanning the image, for example into a computer.
-

- 35 Preferably the step of forming the mould is carried out by a high speed three axis numerically controlled engraving machine. This can be loaded with the relative intensity values of the desired mould, and

can cut any desired number of moulds. Alternatively, the mould may be formed by a laser cutting machine, or by spark-erosion.

5

The mould is preferably formed from metal which is able to withstand the high temperature of the molten plastics material from which the article is to be formed, and which has a long life to allow for repeated
10 mouldings.

It is preferred that a number of moulds are formed from a single mould block to allow a large number of articles to be moulded simultaneously.

15

In an alternative aspect of the present invention, a plastics article can be formed by determining the relative intensity at different points of an image, and machining the plastics article from a
20 translucent plastics material so that the plastics article has a relief such that the thickness corresponds to the different intensities of the image.

This method of forming plastics articles does
25 not allow for the same economy of scale and mass reproduction associated with the first aspect, but is able to produce limited quantities of articles having a specific design. For example, a person's image can be obtained from a digital camera or from a scanned
30 photograph, and machined into a plastics article.

This will be difficult to replicate, and so can be used as a security or identification device.

According to a further example of the present
35 application, there is provided a plastics article having different thicknesses at different positions corresponding to the relative intensity of an image, in

which the plastics article transmits or emits light with an intensity corresponding to the thickness of the material.

5

The material from which the plastics articles are formed should be transparent or translucent, for example may be polystyrene, polypropylene, styrolux, clear ABS or acrylic. The plastics material is preferably filled with a suitable filler material such as china clay, chalk or other filter to give the desired effect.

The plastics material may include luminescent particles or may be coated on the back by a luminescent layer. In this case, the luminescent particles can emit light, and it may therefore be possible to view the image without light being shone through the article. Where luminescent particles are included, the lighter parts of the image may correspond to the thicker parts of the article and the darker parts to the thinner parts as, in this case, in the thicker regions there will be a greater amount of luminous particles and therefore there will be a brighter section.

25

The article may be coloured. In this case, the article may be coloured with a single colour to give an overall tint, or there may be different colours at different parts of the article to give parts of different colour.

30

Where the colour is a single colour, this may be achieved by including pigment in the plastics material used for the moulding. Alternatively, a coloured layer may be formed on a surface of the article. One surface of the article, for example the rear surface, will usually be planar, and therefore a coloured layer can be

35

formed on this surface easily, for example by transfer or sublimation printing or by an ink jet or silk screen printing technique. This will acts as a filter to the
5 light passing through the article.

The article may be formed from heat sensitive material. In this case, the image may only be seen when the article is heated. For example, if the article is
10 formed into a lamp shade, it may be heated by the lamp to become translucent.

The plastics article according to the present invention can be used for a number of purposes, including
15 character promotions, key rings, inserts to be provided in cereal packets, light shades, plates, cups, pictures etc. By use of suitable processing techniques, the article may be a non-flat or three-dimensional article. It is also possible to produce a stereoscopic image by
20 having two side by side articles having substantially the same image but from a slightly different perspective, each of the images being viewed by a different one of the viewer's eyes.

25 An example of the present invention will be described in accordance with the accompanying drawings, in which :

Figure 1 shows a schematic view of the system
30 for forming the plastics article; and,

Figure 2 shows a cross-section through a mould for forming a plastics article.

35 As shown in Figure 1, an image 1, for example a photograph or painting, is scanned by a scanner 2 to convert the image 1 into electronic data which

corresponds to the image 1. The data corresponding to the scanned image is input to a processor 3.

Alternatively, the image may be generated initially in electronic form, for example using a graphics package, or
5 may be loaded from a store of pre-converted or generated images, for example from a CD-ROM, or downloaded, for example from the Internet.

10 The processor 3 analyses the data corresponding to the image to determine the relative intensity, i.e. the relative darkness or lightness, at different points or pixels of the image. This intensity information is provided to a numerically controlled milling machine
15 which is able to use the intensity data to machine one half 11 of a mould in which the depth of the mould at different positions corresponds to the relative intensities of the original image. In a preferred example, the mould has a greater depth where the
20 corresponding position of the original image has a low intensity (i.e. where the image is dark), and has a shallower depth where the corresponding position of the original image has a high density (i.e. where the image is light).

25

The machined mould half 11 and an associated mould half 10 having a generally flat surface, are placed together to form a mould cavity, and plastics material is injected into the mould cavity. The plastics material
30 may be polystyrene, polypropylene, styrolux, or clear ABS. To make the plastics material translucent, a filler material such as china clay, chalk or other filter material is added to the plastics before this is injected into the mould cavity.

35

When the plastics material has set, it is removed from the mould. The resulting article will be

translucent, and will have a greater thickness in those areas corresponding to darker areas of the original image than the areas corresponding to the lighter areas of the original image. When light is shone through the article from behind, the light is transmitted through the thinner parts of the article more easily than through the thicker parts of the article, and therefore the thinner areas appear lighter than the thicker areas. This corresponds generally to the light and dark areas of the original image, and therefore an image corresponding to the original image can be seen.

The article may be coloured on the back by any suitable printing technique, for example by ink jet printing. In this case, the colour is easy to apply as it is applied to the flat rear surface of the article. The coloured layer on the back of the article acts as a colour filter which only lets light of selected wavelengths pass through the layer and hence through the translucent article, and therefore the light viewed through the article is of certain colours. Where the rear of the article is coloured substantially entirely with a single colour, the whole image viewed through the article will have a colour tint, however it is preferred that the rear of the article is selectively coloured with areas of different colour. This allows the light transmitted through different parts of the article to be of different colours, which may correspond to the colours of the original image.

Alternatively, a coloured pigment may be added to the plastics material before this is injected into the mould. In this case, the pigment within the plastics material will act as a filter to allow only light of certain wavelengths to be transmitted to form the view image.

It is also possible to add a luminescent pigment to the plastics material used to injection mould the article. In this case, it is not necessary for a
5 separate back light to be used to view the article, since the article will itself emit light. In this case, the mould is made in reverse to that described above, with the areas corresponding to the lighter sections of the image being formed more deeply than the areas
10 corresponding to the darker areas. In this case, the plastics article moulded by the mould will be thicker in those areas corresponding to lighter areas of the original image, and therefore will have a greater amount of luminescent pigment, and therefore will emit more
15 light than the thinner areas corresponding to the darker regions of the original image which will have less luminescent material and therefore will emit less light.

The injection moulded articles according to the
20 present invention, which, due to the method of manufacture can be formed inexpensively and in large numbers, can be used in many different applications, for example, but not limited to, character promotions, key rings, inserts to be provided in cereal packets, light
25 shades, plates, cups, and pictures.

It may also be possible to form a plastics article having variable thickness or contour corresponding to the relative intensity of an original
30 image by engraving the article directly, for example using a CNC machine, in the same way as described above for forming the mould. In this case, it would be simple to make one-off items, for example it would be possible to convert an image of a person's face into data relating
35 to the relative intensity of the image, and directly engrave a plastics article with different thickness regions corresponding to the different intensities of the

image of the person's face. This could be used as a security device, for example as an identification card, which would be very difficult to forge.

THIS PAGE BLANK (USPTO)




Figure 1




Figure 2

PCT/GB 99/01936 - 18 JUN '99

LOYD - WSE, TREGGAR + CO - 9821658.3

THIS PAGE BLANK (USPTO)
